

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 July 2002 (11.07.2002)

PCT

(10) International Publication Number
WO 02/053696 A1

(51) International Patent Classification⁷: C11D 17/04,
B65D 81/32, 65/46, 75/58

(21) International Application Number: PCT/EP01/15403

(22) International Filing Date:
18 December 2001 (18.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/749,963 28 December 2000 (28.12.2000) US

(71) Applicant (for AE, AG, AU, BB, BZ, CA, CY, GB, GD, GH, GM, IE, IL, KE, LC, LK, LS, MN, MW, NZ, SD, SG, SL, SZ, TT, TZ, UG, ZA, ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).

(71) Applicant (for AL, AM, AT, AZ, BA, BE, BF, BG, BJ, BR, BY, CF, CG, CH, CI, CM, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, FR, GA, GE, GN, GQ, GR, GW, HR, HU, ID, IS, IT, JP, KG, KP, KR, KZ, LR, LT, LU, LV, MA, MC, MD, MG, MK, ML, MR, MX, MZ, NE, NL, NO, PH, PL, PT, RO, RU, SE, SI, SK, SN, TD, TG, TJ, TM, TR, UA, UZ, VN, YU only): UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

(71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).

(72) Inventors: GIBLIN, Edward, John; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). HSU, Feng-Lung, Gordon; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). MCDONALD, Janet; 29 South Lake Drive, Stamford, CT 06903 (US). SASO, Corinne; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). RAIBLE, Duane, Anthony; Unilever Home & Personal Care USA, 325 North Wells Street, Chicago, IL 60610 (US).


(74) Agents: ELLIOTT, Peter, William et al.; Unilever PLC, Patent Department, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: LAUNDRY PRODUCT



(57) Abstract: A new pouch for laundry products and the combination of pouch and laundry product. The pouch includes a tearing notch or a length of weakness, which may comprise a tear tape, permitting manual opening of the pouch prior to tossing the pouch into the washing machine. By tearing open the pouch it is possible to direct liquid or gelled detergent onto clothes for pretreating stains. The remainder of the product, in a second chamber, e.g. liquid, gel or solid, eg. a powder, is retained in the pouch until release during wash. In this respect, it is preferred that at least part of the pouch is a water soluble film to promote release of product during washing in the washing machine and to minimize residue left from the pouch at the conclusion of the wash. The pouch of the invention preferably comprises at least two chambers, one of the chambers being openable by manual tearing along a tearing notch or a line of weakness. In accordance with another embodiment of the invention, a pouch with one or more chambers is provided which narrows to a nozzle for dispensing of product.

BEST AVAILABLE COPY

WO 02/053696 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

- 1 -

LAUNDRY PRODUCT

5 Recently, laundry tablets, a different product form for
laundry washing, have been introduced commercially and well
received by consumers. This is believed to demonstrate the
desirability of unit dose products which can be tossed into
the washing machine. The popularity of another form of
10 laundry product, liquid detergents, can be attributed in
part to the ability of consumers using such products to
pretreat selected areas of clothing which are deemed to
require a higher level of cleaning. A disadvantage of
laundry tablets is that the option of pretreating selected
15 areas of clothing is not available to consumers in this
product form.

Various laundry products in single or dual compartment
pouches, or in dual chambered bottles or have been disclosed
20 over the years.

Muysson, U.S. Patent No. 5,164,178 discloses solid granular
deodorant consisting of hydrated calcium sulfate base,
essential oils absorbed onto the granular base and micro
25 capsules filled with another portion of essential oils. The
granular deodorant is packed in a sealed pouch which has
micro holes covered by a removable adhesive tape.

A laundry cleaning gel product is sold in Europe in a water-
30 soluble pouch. The base is vacuum-formed, filled, and then
sealed with a "lidding" film.

- 2 -

Peterson et al., U.S. Patent No. 5,776,877 is directed to a liquid peracid precursor composition for delivering a bleaching and cleaning material in which the composition combines a dispersant medium which includes an emulsifier and a dispersed phase that comprises the peracid precursor. A bottle or container comprised of two chambers may be used.

Scheuing et al., U.S. Patent No. 5,681,805 discloses a bottle having two chambers for a liquid peracid precursor composition.

Dunlop et al., U.S. Patent No. 3,198,740 discloses a package of a water-soluble film of polyvinyl alcohol filled with detergent composition. The compositions which are filled in the water-soluble packets are non-liquid, water-soluble synthetic detergents which contain sodium tripolyphosphate and a hydrated salt. Generally such compositions contain one or more anionic synthetic organic detergents. Other ingredients to be filled in the water-soluble packets can be inorganic builders in addition to sodium tripolyphosphate suds builders, alkali metal silicates, bleaching ingredients, and other minor ingredients such as pigments, dyes, perfumes, redeposition inhibitors, optical fluorescers, tarnish inhibitors and other useful additives.

Bianco et al., U.S. Patent No. 3,374,195 relates to polyvinyl alcohol compositions containing a plasticizer, and to plasticized polyvinyl alcohol films produced therefrom. Use of polyvinyl alcohol films in the manufacture of water-soluble bags or pouches for such materials as detergents, bleaches, insecticides, etc. is mentioned. The package may

- 3 -

be dropped in hot or cold water wherein the bags disintegrate and the products are dispensed.

Gray, U.S. Patent No. 3,528,921 discloses a bleaching packet wherein a dry bleach composition is contained in a packet of water-soluble polyvinyl alcohol film. In use, the entire packet is dropped into a washing machine containing water and clothes to be bleached without any need for pre-measuring by the person doing the washing. The product container, i.e., the polyvinyl alcohol film, is said to contribute considerable soil anti-redeposition properties to the system and thus the packets are said to be especially suited for use in conjunction with soap and detergent products in connection with the washing and bleaching of soiled clothes.

Kerry et al., U.S. Patent No. 4,681,228 is directed to toxic products situated in a closed inner container consisting of a water-soluble flexible material, the inner container being placed within a closed container consisting of a flexible material which is resistant to water. In order to release the packed substance, the outer container is cut open and the inner container is deposited in water with a film of the inner container and the toxic filling dissolved. Toxic substances are substances, such as agricultural chemicals, which must not come into contact with the human body, both during the filling and packaging and during the transport of the packages and release of the toxic substances from the packages. The water-soluble material is, for example, polyvinyl alcohol and it is filled with a water-soluble

- 4 -

toxic powder or granular product. A tear line 7 is included.

Ball, U.S. Patent No. 3,737,027 is directed to a composite
5 pack for a two component hardening resin comprising two flexible frangible containers, one within the other. The pack is for stabilizing and reinforcing rock formations and for securing elements in bore holes.

10 Clarke et al., U.S. Patent No. 4,188,304 discloses a detergent product which comprises a particulate detergent composition contained within a closed water-insoluble bag which has a water sensible seal. The contents of the bag are discharged on contact of the bag with water. It is said
15 that, if desired, the bag can be formed with more than one separate compartment for different detergent ingredients, or the bags may be formed in a conjoined manner, for instance in a strip to facilitate dosing of different numbers of the bag as appropriate for the wash conditions. It is said that
20 any detergent composition in powder form can be packaged to advantage in the product of the '304 invention.

Davies et al., U.S. Patent No. 4,410,441 discloses a fabric treatment product which is in the form of a bag having at
25 least two compartments containing particulate fabric treatment compositions. The bag has a first outer wall and an intermediate wall of water insoluble, but water permeable material, and a second outer wall of water impermeable water insoluble plastic sheet. In the washing machine, the wash
30 water first enters the compartment bounded by the first outer wall which is water permeable and dissolves and

- 5 -

disperses out its contents. The water subsequently penetrates the intermediate wall to enter the second compartment and dissolve or disperse out its contents. The first compartment may, for instance, contain detergent
5 whereas the second compartment may contain fabric softener.

Cornelissens et al., U.S. Patent No. 4,622,161 is directed to a dosing unit comprising a detergent and/or bleaching agent contained in a sachet which entirely or partly
10 consists of a sealable substrate and is provided with one or more seams that are sealed with a water sensitive coating composition. It is said that the moment at which the sachet opens up is to a great extent independent of the agitation and heating up behavior of the dishwashing machine. This is
15 obtained by using a coating composition comprising an anionic and/or nonionic water binding polymer and a cationic polymeric adhesive.

Anderson et al., U.S. Patent No. 4,776,455 is directed to a
20 multi compartment sachet product for the washing machine or dishwasher comprising a first compartment capable of releasing its contents (solid or liquid) within three minutes from the start of the wash process and a second compartment of water permeable material with a pore-
25 occluding coating and/or in the form of a sachet so that the release of its contents (powder), is gradual and is delayed for at least five minutes from the restart of the wash process. The seal of the first compartment may be, for example, sensitive to water temperature or agitation such as
30 the mechanically weak heat seal of EP 11500 or EP 40931.

- 6 -

Oakley, U.S. Patent No. 2,760,942 discloses a heat sealing coating composition which is water soluble. The compositions contain polyvinyl alcohol and at least one of urea and dextrose. Bond strengths ranging from poor to good, are given for various coating formulations. In one case, a slight seal is obtained. Bond strength in g/in is given for various runs. It is said that packaging films sealed in accordance with the invention can be used to package detergents, food stuffs, etc.

10

Schwadtke et al, U.S. Patent No. 4,139,475 is directed to a laundry treatment agent for use in a mechanical laundry dryer comprising a paste of fabric softening substances, textile anti-static, disinfectant and optionally odorants mixed with a liquid, in a package of film material having a pillow-like form with one side impermeable to the substances and the other side having a plurality of slits therein. The slits are of such dimensions that at room temperature and in the absence of pressure on the article, the slits are substantially closed and obstruct the issuance of the paste from the article. Under the influence of the laundry moved in the laundry dryer and the heat prevailing there, the slits open and gradually release the effective substance.

15

20

25

Falou et al., U.S. Patent No. 5,132,036 discloses a single or multi-compartment sachet containing a particulate bleaching composition which may optionally include detergent ingredients. The sachet system is said to denote for the purposes of the '036 invention any discreet sachet structure. A plurality of single compartments may be joined

30

- 7 -

together in an easily separable manner, for example via a perforated region.

Preferably the '036 sachet system is designed such that the contents will be released at or very shortly after the time of addition to the wash liquor, although it may sometimes be desirable for at least one compartment or sachet thereof to give a delayed or controlled release of treatment agent. The sachet systems may be of a non-opening type where the contents are leached out of the wash liquor through pores in the sachet substrate, or of the opening type where the sachet opens or disintegrates on contact with the wash water. An alternative to a water labile seal is a mechanically weak heat seal which is disrupted by the mechanical action of the washing machine.

GB 2 000 177 is directed to a detergent composition which may be put up in sachet. The sachet may be completely or partly made of a material permeable to or disintegrating in water. The sachet may consist of a material which does not disintegrate in water and which is closed with a strip of material which does disintegrate in water. Alternatively, the sachet may be closed by seams joined with a material that disintegrates in water.

Haq, U.S. Patent No. 4,515,703 discloses an article suitable for wiping a surface in order to deliver an active material to the surface, or for gradually releasing an active material, such as a bubble bath composition. The article comprises a first substrate layer and a second substrate layer so bonded together as to create a plurality of

- 8 -

compartments therebetween, at least some of the compartments containing active material and at least some of the compartments being provided with one or more perforations in one or each of the substrate walls defining the

5 compartments. The active material may be in any suitable form, for example, a solid block, a powder, a gel, a liquid or any combination of these. It is said that the distribution of perforations among the compartments may be either regular or irregular as desired. Different

10 compartments may be provided with different numbers of perforations so that contents of different compartments will be released at different rates.

EP 312 277 is directed to a sealable sachet having a seal

15 which is mechanically strong in the dry state but disintegrates in water at temperatures of 40°C or below under the influence of mechanical agitation. Preferably the dry bond formed between the wall and the sealant composition should be strong enough that eventual failure of the bond on

20 the application of a pulling force will result in tearing of the non-heat sealable material rather than rupture of the bond. The invention is said to be of special applicability to the home laundry process. Bond strengths are given.

25 EP 011 500 is directed to particulate detergent compositions contained within a closed bag of sheet material. The bag is constructed so as to open and discharge its contents under mechanical action in a washing machine in use. The seams of the bag may be heat sealed or cold pressured sealed so that

30 at least one seam will burst open in use. The means for opening the bag and discharging its contents under the

- 9 -

influence of mechanical action in the washing machine during use may be constituted by closing the bag with at least one weak seal. The mechanism whereby the bag opens depends on the number of factors primarily the strength of the weak seal, in particular its peel strength.

The material used to form the bags should be water insoluble, but preferably water permeable. The preferred bags open by bursting of at least one weak seal which is strong enough to resist opening during transport and manual handling but which will open readily when the bag is agitated in the washing machine. The seals are preferably formed by heat sealing or by cold pressure sealing. Alternatively, at least part of the bag may be made of a material which will disintegrate in use. A still further method of enabling the bag to open and discharge its contents in use is to form the sidewalls of the bag with weakened areas, e.g. in the form of linear slit perforations with a manually removable protective strip positions thereover. Opening of the bag then occurs by bursting at the weakened areas.

It is said that any detergent composition in particulate form can be packaged to advantage in the products of the '500 invention. As an alternative to fully formulated detergent compositions, the bags may contain any one or more of the following treatment materials: bleaches, bleach precursors, fabric softeners, starch, perfumes, antibacterial agents, anti-static agents, whitening or bluing agents, stain removing agents and the like. Perfumes, bleaches, bleach precursors and cationic fabric

- 10 -

softening agents are mentioned. The products of the invention are said advantageously to be used for detergent powders containing insoluble ingredients. Dry mixing of the detergent composition is mentioned. If desired, the bags
5 can be formed with more than one separate compartment containing different detergent ingredients at least one of which compartments is adapted to opening in the wash.

EP 040 931 is directed to a fabric treatment product for use
10 in a washing machine comprising a bag formed of water insoluble, water impermeable synthetic plastics sheet material containing a fabric treatment composition comprising a liquid, the bag having a weak seal that will be opened by the mechanical action of a washing machine. The
15 opening seal can comprise a mechanically weak heat seal. The bags may consist of a single compartment or include at least one further external wall defining one or more further compartments. The further wall may be formed of a similar material to the main walls of the bags, in which case it
20 will also need an opening seal. Alternatively, the further wall may be formed of a water soluble film material such as polyvinylacetate/polyvinylalcohol or a water permeable water insoluble material, for example, a fibrous sheet material. Particulate treatment compositions may be present. If
25 desired, the sheet material used to form the bag can be marked or tagged so that it can be easily recognized among the washed fabrics, for example, the material may be printed with a simulated fabric pattern such as a check or gingham.

30 Bianco et al., U.S. Patent No. 3,413,229 is directed to polyvinyl alcohol compositions containing a plasticizer

- 11 -

useful for laundry packets containing detergents and/or bleaches.

Falou et al., U.S. Patent No. 5,160,654 discloses a product
5 for treating fabrics in a washing machine in the form of a
sachet having at least two compartments. Preferably the
sachet is composed of water insoluble, preferably water
permeable, sheet or film material and is closed by one or
more sheets sensitive to water and/or mechanical agitation.
10 In a second preferred embodiment the sachet is comprised of
a water soluble film material. The detergent composition is
divided into two or more powder components which are packed
separately in the appropriate compartments of the sachet.
Half dose units may be joined together in an easily
15 separable manner, for example, via a perforated region.

EP 293 139 is directed to a particulate laundry composition
releasably contained within a closed, single or multi
compartment sachet having a frangible seal, the sachet being
20 formed of a water insoluble, calender bonded or calender
finished, non woven bonded substrate material, which is a
thermo-bonded fibrous or filamentous substrate wherein the
fibers of filaments are bi-components fibers having a
polyester core and a polyethylene sheet. The frangible seal
25 or seals are most conveniently formed using heat bondable,
water soluble or water dispersible adhesives.

EP 163 417 is directed to bleach products for use in the
washing machine and disposed in a closed bag containing a
30 particulate bleach composition. The bag is formed of sheet
material having pores large enough to render it water

- 12 -

permeable, but small enough to confine the bleach composition within the bag.

EP 836 108 is directed to bleaching washing agents.

5

U.S. Patent No. 6,037,319 discloses water soluble packets with liquid cleaning concentrates.

10 The present invention is directed to a new pouch for laundry products and to the combination of pouch and laundry product. The pouch includes a tearing notch or a length of weakness, which may comprise a tear tape, permitting manual opening of the pouch prior to tossing the pouch into the
15 washing machine. By tearing open the pouch it is possible to direct liquid or gelled detergent onto clothes for pretreating stains. The remainder of the product, in a second chamber, e.g. liquid, gel or solid, e.g. a powder, is retained in the pouch until release during wash. In this
20 respect, it is preferred that at least part of the pouch is a water soluble film to promote release of product during washing in the washing machine and to minimize residue left from the pouch at the conclusion of the wash.

25 The pouch of the invention comprises at least two chambers, one of the chambers being openable by manual tearing along a tearing notch or a line of weakness. That chamber preferably includes a liquid detergent or less preferably a gel detergent. Thus by tearing open the first chamber, it
30 is possible to pour out the liquid detergent (squeeze out in the case of a gel) and pretreat the clothes. The product

- 13 -

contained within the second and optionally further chambers is preferably dispensed in the washing machine during washing. Again, a water soluble pouch material would promote dispensing during washing.

5

In accordance with another embodiment of the invention, a pouch with one or more chambers is provided which narrows to a nozzle for dispensing of product. Preferably the nozzle includes a notch or slits or a length of weakness such as a
10 line of weakness to permit manual tearing open of the nozzle and dispensing of product. Preferably the interior of the chamber which is in communication with the nozzle contains a liquid product which can be readily dispensed through the open nozzle to pretreat desired areas of the clothing.
15 Alternatively, the portion of product in the chamber which is in communication with the nozzle may be a gel which can be dispensed by exerting pressure on the chamber once the nozzle has been opened. Preferably, any chambers in the pouch which are not openable by manual tearing should at
20 least permit dispensing of product at some point while the pouch is in the washing machine. Options include making the pouch of water soluble material, making the pouch of water permeable material, making the seals of a water soluble material, and/or making seals openable by mechanical
25 agitation and/or heat during washing.

The nozzle of the pouch of the invention may be disposed in the center of one side of the pouch, in a corner of a pouch, or otherwise. The nozzle may be funnel-shaped or it might
30 be S-shaped or it may assume a further shape. The pouches

- 14 -

of the invention will generally be rectangular, but other forms such as triangular pouches may be used as well.

The pouches of the invention may be prepared from a
5 continuous tube of polyvinyl alcohol film, or other suitable material, which is filled, then sealed, then filled, then sealed.

The invention is also directed to the processes of making
10 the pouches and also to the process of using the pouch whereby the pouch is manually torn open prior to tossing into the washing machine and clothing is pretreated with product from at least one of the chambers.

15 For a more complete understanding of the above and other features and advantages of the invention, reference should be made to the following Detailed Description a number of Embodiments and to the accompanying drawings.

20

Fig. 1 is a top plan view of a pouch according to the invention.

Fig. 2 is a top plan view of an alternate pouch according to
25 the invention.

Fig. 3 is a top plan view of a still additional embodiment according to the invention.

30 Fig. 4 is a top plan view of another embodiment according to the invention.

- 15 -

Fig. 5 is a top plan view of a further embodiment according to the invention.

5 Fig. 6 is a top plan view of a still further embodiment according to the invention.

Fig. 7 is a top plan view of another pouch according to the invention.

10

Fig. 8 is a top plan view of another pouch according to the invention.

15

Fig. 9 is a top plan view of a further embodiment according to the invention.

Fig. 10 is an elevational view of pouches being filled.

20

Fig. 10a is a top plan view of a polyvinyl alcohol film which has been formed into pouches suitable for use in the present invention.

Fig. 10b is a section along the lines-10b-10b of Fig. 10a.

25

Fig. 10c is a top plan view of an individual heat sealed chamber containing a gelled detergent.

Fig. 11 is a cross section of Fig. 1 according to lines 11-11.

30

- 16 -

Referring particularly to Fig. 1, pouch 10 includes two compartments 12 and 14 separated by heat seal 16. First chamber or compartment 12 narrows to nozzle-forming conical aspect 18 at one end of the chamber.

5

Pouch 10 is heat sealed along its periphery 20, having been formed from a cylindrical sheet of polyvinyl alcohol. A tearing notch 22 in the form of a v-notch or slit is disposed in the heat seal of pouch 10 adjacent nozzle 18.

10 Contained within chamber 12, which is in communication with nozzle 18, is a liquid detergent formulation. Contained within chamber 14 is a powdered detergent formulation.

15 A length of weakness, such as a (straight) line of weakness which promotes tearing along a controlled path, may be used in place of, or in conjunction with the tearing notch.

In operation, the consumer tears open chamber 12 at notch 22 prior to tossing pouch 10 into the washing machine. This
20 permits the consumer to direct liquid detergent onto particularly soiled aspects of the clothing, as desired. The remaining portion of the pouch is then tossed into the washing machine. The water soluble aspects of chamber 14 permit dispensing of the powder into the wash while the
25 washing machine is in operation.

The product of chamber 12 may also be a gel. The product of chamber 14 may be in any physical state.

30 Preferably, at least 40% of the surface area of chamber 14 is made from water soluble film, such as polyvinyl alcohol.

- 17 -

Alternatively, the seal along the periphery of chamber 14 and/or the separating seal 16 between chambers 14 and 12 may be fabricated from a mechanically weakened seal and/or a water soluble seal. Also, chamber 14 may be formed from a water permeable substance such that the powdered detergent will be leached from the chamber once the pouch has been placed into the wash. Preferably, the entire pouch is made of a water soluble material such that little or none of the pouch and its contents, preferably none of the pouch and its contents, remains after washing has been completed.

Fig. 2 represents an alternate embodiment wherein the product is in a single chambered pouch 30 having a nozzle 31. The laundry product can be a liquid, powder or gel.

The pouch of Fig. 3 is similar to that of Fig. 1, except that the nozzle is disposed in a corner of the (rectangular) pouch.

The pouch of Fig. 4 is similar to that of Fig. 3, except that the seal dividing the chambers is disposed perpendicularly to that of Fig. 3.

The pouch 60 of Fig. 5 is similar to pouch 40 of Fig. 3 except that an S-shaped nozzle 62 is used for better control of flow.

In the embodiment of Fig. 6, an S-shaped nozzle 66 is used in pouch 68. Each chamber includes a liquid detergent or other laundry treating composition. In this embodiment, use

- 18 -

of two chambers permits dosing of a pretreatment amount and a second washing amount.

In the embodiment of Fig. 7, pouch 80 includes two notches, large notch 82 and smaller notch 84 to assist in opening the first chamber 86. Second chamber 88 is separated from first chamber 86 by heat seal 90. Chambers 86 and 88 are made of a water soluble, polyvinyl alcohol film.

In Fig. 8, pouch 90 has a triangular body which narrows into wedge- or funnel-shaped nozzle 92 which is adjacent line of weakness notch 94.

Pouch 100 of Fig. 9 is also triangular and features recessed nozzle 102 having notch 104 which opens from chamber 106 to dispense liquid product. Heat seal 108 separates the polyvinyl alcohol chamber 110 from polyvinyl alcohol chamber 106. The body of pouch 100 is triangular and the nozzle is recessed inwardly from the corner which would otherwise be formed by the sides 112 and 114 of the pouch.

The pouch may be formed from a continuous tube of polyvinyl alcohol film or, as seen in Fig. 10, especially 10b may be formed from two films 370, 380. One end of chamber 122 is formed by sealing at 124. As illustrated in Fig. 10, other heat seals 125 are also present prior to filling. Openings 300 are provided to accommodate multiple filler nozzles 310. Notches 330 are provided to facilitate opening of one or more of the chambers. Lines of weakness, such as perforated lines 340 are provided to facilitate separations of the chambers. After chambers 122, 130, 138, etc. are filled

- 19 -

with liquid product 126, the nozzles 310 are withdrawn and a third side of each of the chambers, is then heat sealed at 128 as seen in Fig. 10a.

5 Referring to Fig. 10, at some point, it may be desirable to separate chamber 130 from chamber 138 adjacent seal line 134 to form pouch 150. Alternatively, the pouch may include only one, or more than two, chambers. For instance, a first chamber may include liquid detergent product for pretreating
10 when the notch is opened. The second chamber may comprise the same or different detergent product contained in a water soluble pouch which dissolves upon placement in the washing machine. Preferably the first chamber is also made of a water soluble film which dissolves in the washer. A third
15 chamber may be provided with fabric softening liquid or solid, and release of product may be deferred to a later time in the washing cycle by use of a water permeable rather than water soluble, film or by use of a seal which is weakened mechanically or chemically so as to release at an
20 appropriate time in the wash cycle.

The pouch shape including nozzle feature would be formed with a shaped heat-sealing form, and the nozzle and notch would be die-cut. This is a form/fill/seal and die-cut
25 operation.

Various combinations of product within multiple chambers are possible, e.g., liquid/liquid, powder/powder, gel/gel, gel/liquid, gel/powder, etc.

30

- 20 -

The pouch of the invention may be used to contain various laundry products, including but not limited to, laundry detergents, fabric softeners, bleaches, bleach precursors, perfumes, antibacterial agents, anti-static agents, whitening or bluing agents, etc. The laundry products may or may not include enzymes and builders. Laundry detergents generally comprise surfactants such as anionic and/or nonionic surfactants. Fabric softeners often include cationic surfactants. Laundry products which may be considered for use in the present invention include those described in U.S. Patent No. 5,132,036 and 4,420,441, the disclosures which are hereby incorporated by reference.

The pouch may take many shapes as viewed in a plan view, such as rectangular, square, round, triangular, figure 8, etc. A notch, slit or perforated line could range in size from 1/16" to 1/2".

The pouch is preferably made of a clear, heat sealable, cold water soluble film such as polyvinyl alcohol. Thickness could range from 1.5 to 3 mils, preferably 2 mils. Other materials from which the pouch can be made include methyl hydroxy propyl cellulose.

It should be understood of course that the specific forms of the invention herein illustrated and described are intended to be representative only, as certain changes may be made therein without departing from the clear teaching of the disclosure. Accordingly, reference should be made to the appended claims in determining the full scope.

- 21 -

CLAIMS

1. A laundry-treatment article comprising:
 - (a) a pouch comprised of a water soluble and/or water-permeable film and having a tearing notch or a length
5 of weakness for manually tearing open said pouch,
 - (b) said pouch containing laundry product:
 - (i) in separate compartments wherein at least one of said
compartments includes the tearing notch or the length of
10 weakness for manually tearing open said compartment.
2. An article according to claim 1 wherein at least one of said products is a liquid at 25°C.
- 15 3. An article according to any of claim 1 or claim 2 further comprising tearing indicia at said notch or said length of weakness.
4. An article according to any preceding claim wherein said
20 notch or length of weakness is positioned to open said compartment which contains the liquid at 25°C laundry product.
5. An article according to any preceding claim wherein said
25 pouch comprises at least two separate compartments one of which includes said notch or length of weakness and the other of which has an external surface area at least 40% of which is made of a water-soluble film.

- 22 -

6. A laundry treatment article according to any preceding claim wherein two of said discrete laundry products include a liquid and a powder.

5 7. A laundry treatment article according to any preceding claim wherein said film is cold water soluble.







8. A laundry treatment article according to any preceding claim wherein said film is clear.

10

9. A laundry treatment article according to any preceding claim wherein said length is curved.


10. A laundry treatment article according to any preceding
15 claim wherein said length is straight.

1/5



2/5

FIG. 7



3/5

FIG. 8







FIG. 9








FIG. 10a




FIG. 10c




FIG. 10b

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/EP 01/15403

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C11D17/04 B65D81/32 B65D65/46 B65D75/58

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C11D B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 011 500 A (UNILEVER NV ; UNILEVER LTD (GB)) 28 May 1980 (1980-05-28) cited in the application claims 1,3,14 page 5, line 5 - line 10 page 5, line 34 - page 6, line 3 page 6, line 26 - line 30	1-10
P, X	WO 01 83658 A (DASQUE BRUNO MATTHIEU ; RAINEAU OLIVIER CHARLES (GB); SOMERVILLE RO) 8 November 2001 (2001-11-08) claims 1-7,10,11 page 1, line 24 - line 29 page 2, line 13 - line 14 page 3, line 18 - line 26 page 5, line 26 - page 6, line 2 page 8, line 8 - line 9 -/--	1-10

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

11 March 2002

Date of mailing of the international search report

21/03/2002

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Rasmusson, R

INTERNATIONAL SEARCH REPORT

Int. Application No.
PCT/EP 01/15403

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 593 952 A (DISPO KOMMERZ AG) 27 April 1994 (1994-04-27) claims 1-6, 10, 13-16 ---	1-10
A	GB 2 000 177 A (AKZO NV) 4 January 1979 (1979-01-04) claims 1, 8-10 ---	1-10
P, A	GB 2 361 686 A (PROCTER & GAMBLE) 31 October 2001 (2001-10-31) claims 1, 2 page 4, line 16 - line 21 -----	1-10

INTERNATIONAL SEARCH REPORT

...on patent family members

International Application No

PCT/EP/15403

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0011500	A	28-05-1980	AT 262 T	15-10-1981
			AU 572207 B2	05-05-1988
			AU 3447784 A	07-02-1985
			AU 534264 B2	12-01-1984
			AU 5292179 A	22-05-1980
			BR 7908912 A	04-08-1981
			CA 1135218 A1	09-11-1982
			DE 2961151 D1	10-12-1981
			EP 0011500 A1	28-05-1980
			ES 486070 D0	16-12-1980
			ES 8101642 A1	16-03-1981
			WO 8001076 A1	29-05-1980
			JP 63039640 B	05-08-1988
			JP 55500900 T	06-11-1980
			MX 150317 A	16-04-1984
			US 4555354 A	26-11-1985
			ZA 7906191 A	24-06-1981
WO 0183658	A	08-11-2001	GB 2361686 A	31-10-2001
			GB 2361707 A	31-10-2001
			GB 2361688 A	31-10-2001
			GB 2361685 A	31-10-2001
			WO 0185898 A1	15-11-2001
			WO 0183658 A2	08-11-2001
			WO 0183657 A2	08-11-2001
			WO 0183667 A1	08-11-2001
			GB 2361690 A	31-10-2001
			WO 0183668 A1	08-11-2001
EP 0593952	A	27-04-1994	DE 9214065 U1	03-06-1993
			EP 0593952 A1	27-04-1994
GB 2000177	A	04-01-1979	AT 374826 B	12-06-1984
			AT 462378 A	15-10-1983
			BE 868474 A1	16-10-1978
			CH 639416 A5	15-11-1983
			DE 2827571 A1	11-01-1979
			DK 285078 A ,B,	28-12-1978
			ES 476032 A1	01-07-1980
			FR 2396076 A1	26-01-1979
			IT 1097284 B	31-08-1985
			NL 7805293 A ,B,	29-12-1978
			NO 782178 A ,B,	28-12-1978
			SE 439780 B	01-07-1985
			SE 7807255 A	28-12-1978
GB 2361686	A	31-10-2001	WO 0185898 A1	15-11-2001
			WO 0183658 A2	08-11-2001

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)